



AF80/AF100  
Medium duty profiles

# Dummy profile AF80 and AF 100

- dummy profile AF80 and AF100 for industrial concrete floor slabs
- for vehicles with pneumatic tires
- alternative to joint cutting
- serves as dummy joint and reference point for final floor height

## Description / Details:

Dummy profile AF80, PVC material, height 80 mm, width 40 mm. For floor slab thicknesses up to 25 cm. Dummy profile AF100, PVC material, height 100 mm, width 40 mm. For floor slab thicknesses up to 30 cm. Dummy profile for medium traffic in LGV halls, underground parking garages etc. Use lean concrete to set joint rail to final height of concrete floor slab. Extension and intersection points by means of connection clips. The profile also serves as reference point for the final floor height and as bench mark for slopes.

## Tender specification:

Construction of dummy joints with dummy profile AF80 / AF 100 or equivalent. Level profile to finished surface height of concrete floor slab. Set profile system on lean concrete one day before concrete placement.

No joint sealing required. Extension and intersection points by means of connection clips.

Profile / Item no.	Profile height	Material	Element lengths	Packing units
AF80	80 mm	PVC	2500 mm	25 RM/500 RM
AF100	100 mm	PVC	2500 mm	25 RM/500 RM

guggemos gmbh  
Iglauer Straße 6  
86316 Friedberg OT Derching  
GERMANY  
Phone: +49(0)821/724103 - Fax: +49(0)821/724105  
www.fugenprofile.de

59

AF80  
AF100